



CDX Structural Plywood

PS1-09 structural plywood, Exposure 1

INDICATIVE DATA — please contact us directly for the manufacturer's spec sheet for your specific order: 718-386-6119 · inquiry@dmlumber.com

Product

Certifications	PS1-09 Structural Plywood · FSC 100%
Certified by	Timber Products Inspection (TPI)
Composition	Softwood plywood bonded with phenolic resin
Wood species	Slash pine / loblolly pine (Pinus elliottii / Pinus taeda)
Bond quality	EXPOSURE 1 (above 80% wood failure average)

Veneer grades

Layer	Finishing	Knots	Knotholes	Splits
Face	Rough	Up to 3"	Up to 2-1/2"	Occasionally up to 1"
Back	Rough	Up to 3"	Up to 2-1/2"	Occasionally up to 1"

Dimensional tolerances

Item	15/32"	19/32"	23/32"
Panel plies	5 plies	5 plies	5 or 7 plies
Minimum thickness	0.438"	0.563"	0.688"

Length and width +0 / -1/8"

Squareness +/- 1/8"

Structural performance

Panel	15/32"	19/32"	23/32"
Span rating	32/16	40/20	48/24
Roof spacing	32"	38.4"	48"
Subfloor spacing	16"	19.2"	24"

Size and packaging

Panel size	2440 x 1220 mm (8' x 4')
Packaging	Panels stacked over wooden skids and tied with 5 or more steel straps.