Laminated Plywood - Core Panel

Hardwood plywood (Albizia falcataria and combi core)

INDICATIVE DATA — please contact us directly for the manufacturer's spec sheet for your specific order: 718-386-6119 · inquiry@dmlumber.com

Product identification

Product: Plywood (Albizia falcataria and combi core) · **Trade name:** Plywood · **Synonyms:** None

Grade: C2 / B2 / B / B / A · CARB Phase 2 compliant

Supplier: D&M Lumber Products, 74 Bowne Street, Brooklyn, NY 11231 · 718-386-6119 · inquiry@dmlumber.com

Description

This panel product contains Albizia falcataria and Shorea sp. with wood components such as other wood veneer, particleboard or medium density fiberboard (MDF) using urea-formaldehyde / NAUF resin.

Potential airborne releases

The product may release very small quantities of formaldehyde (CAS no. 50-00-0) in gaseous form. Emissions decrease through time as the panels age. Manual or mechanical cutting or abrasion processes performed on the product can result in generation of wood dust.

Physical data

Boiling point, vapor density, melting point, vapor pressure, evaporation rate and pH: not applicable. Volatiles by volume: 0%.

Appearance and odor: Light to dark color; color and odor occur.

Resin data (as reported by the mill)

pH (paper / 25 °C) 7.20 · viscosity (25 °C) 1.06 · gelation time (35 °C) 54 · water solubility (25 °C) >20 · resin content (105 °C) 50 · free formaldehyde 1.20 · specific gravity (25/4 °C) 1.190

First aid

Inhalation: Remove to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.

Ingestion: Not applicable.

Disclaimer

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. No warranty of any kind, express or implied, is made concerning the accuracy or completeness of the information and data herein. It is incumbent upon the user to obtain the most up-to-date information.